



PW PLATFORMS



Ladders Work Platforms Industrial Stairways
Cage Ladders Crossover Bridges Cylinder Cabinets


Custom Designed Access Products

800-231-9936

www.pwplatforms.com

Custom Design

There is no job too big or too small for PW Platforms. We have manufactured custom designed products for decades. Give us a call to discuss your problem. We normally provide quotations to our customers within 24 hours. Below is only a few photos we could gather of our custom designed products.



Call to Discuss Your Custom Solution



Standard Information

Origin

All products ship from our plant in Houston, TX 77051

Prices

There are no prices shown in this catalog. Please consult your separate Dealer Price List.

Terms

Terms of payments are net 30 days from date of invoice with approved credit.

Any orders with open invoices over 60 days old will be placed on hold until past due invoices are paid.

A charge of 12% per month will be applied to all invoices past due. This will be calculated from the 31st day.

Shipping

All products ship from our plant in Houston, TX 77051. Shipping is a separate cost from catalog prices.

Some larger products require a Crating Charge for added protection. *See page 4.*

Freight Damage

It's the customer's responsibility to file all damaged freight claims. Before accepting goods from the shipping company, check the items and make note of any damages or shortage of items. Have the shipper state this in writing on the freight bill. If damage or shortage of items is found after goods have been accepted, this is called "Concealed Damage". You must notify the shipper immediately.

Return Policy

All items marked "Special" are considered Non-Returnable and Non-Refundable items.

Items must be in new condition and accepted in writing by PW Platforms with an RGA#.

Minimum 20% restocking fee will be made and return freight will not be paid by PW Platforms.

Ordering Information

Minimum order value of \$25 or more.

Contact & Mailing Information

Toll-Free 800-231-9936

Fax 713-943-1412

2906 Holmes Road

Houston, TX 77051

About Us

USA Made with Texas Pride!

Family owned and operated for over 50 years



- All-American materials
- Expedited production
- Custom fabrication




Buyers Guide

Materials - Steel or Aluminum. Call for Stainless Steel or Galvanized.

Finish - Gray enamel finish is standard. Yellow enamel is available. Call for special paint colors.

Treads - Our products come in the following tread designs.



Dry indoor areas



Wet, oily and muddy areas



Office areas

Locking Types



Casters retract with weight on the first step.
Pull the handle to release lock.



Spring compresses with weight on first step
Legs retract with relief of weight.

Ladder and Platform Measurements

A - Step Height or Platform Height

B - Step/Platform width

C - Platform depth

D - Overall depth

E - Overall width

*Overall height is A + handrail height



All products meet or exceed
OSHA & ANSI Requirements
unless otherwise stated as a
“special needs” item.



Shipping Guide

All of our products ship using the industry standards for ladders and work platforms. After a thorough Quality Check is performed on each product, they are either palletized or crated. Shrink wrapping and padding adds an extra layer of protection. Below are some examples:



Rolling Ladder - Knock Down



Crossover - Knock Down

Rolling Ladder
All-Welded



Crossover - All-Welded



Double Entry - Knock Down

Office Step Ladder
UPS / Fedex



Work Platform - All-Welded



Roll-A-Fold

For ladders and stairways over 16-steps high, a **Protective Crate** is necessary. Crating charges are applied.

All of our products ship with a Yellow Safety & Use Label and a Red PW Platforms Label with serial #.



Long yellow sticker placed on lip of step. OSHA compliance noted

Rolling Safety Ladder



Standard Features

- 57 or 50 degree slope
- 30", 24", or 18" wide steps
- 5 steps and higher are "Lock-Safe"
- 4 steps and shorter are "Spring-Loaded"
- Rubber tips at stabilizing legs
- 14" deep top platform
- 300 lbs load rating
- 1" square steel construction
- 30" handrails if equipped
- Gray industrial enamel finish

Optional Items Available

- 500 lbs load rating HEAVY DUTY
- Deeper top platform
- Larger casters or Easy-Turn
- Top walk-off access
- California OSHA compliant

57° STANDARD SLOPE

Item #	Steps	Platform Height	Step Width	Base W x D	Weight
Item #s with an "H" have 30" Handrails					
BS1S18	1	10"	18"	20" x 14"	15 lbs
BS1S30	1	10"	24"	26" x 14"	17 lbs
BS1S35	1	10"	30"	32" x 14"	19 lbs
BS2S18	2	20"	18"	20" x 20"	22 lbs
BS2S30	2	20"	24"	26" x 20"	26 lbs
BS2S35	2	20"	30"	32" x 20"	28 lbs
BS2SH18	2	20"	18"	20" x 20"	32 lbs
BS2SH30	2	20"	24"	26" x 20"	34 lbs
BS2SH35	2	20"	30"	32" x 20"	36 lbs
BS3S18	3	30"	18"	20" x 28"	34 lbs
BS3S30	3	30"	24"	26" x 28"	36 lbs
BS3S35	3	30"	30"	32" x 28"	40 lbs
BS4S18	4	40"	18"	20" x 34"	38 lbs
BS4S30	4	40"	24"	26" x 34"	40 lbs
BS4S35	4	40"	30"	32" x 34"	42 lbs

50° EASY SLOPE

Item #	Steps	Platform Height	Step Width	Base W x D	Weight
PW50-2S18	2	20"	18"	20" x 26"	21 lbs
PW50-2S30	2	20"	24"	26" x 26"	29 lbs
PW50-2S35	2	20"	30"	32" x 26"	31 lbs
PW50-2SH18	2	20"	18"	20" x 26"	35 lbs
PW50-2SH30	2	20"	24"	26" x 26"	37 lbs
PW50-2SH35	2	20"	30"	32" x 26"	39 lbs
PW50-3S18	3	30"	18"	20" x 32"	37 lbs
PW50-3S30	3	30"	24"	26" x 32"	39 lbs
PW50-3S35	3	30"	30"	32" x 32"	44 lbs
PW50-3SH18	3	30"	18"	20" x 32"	40 lbs
PW50-3SH30	3	30"	24"	26" x 32"	42 lbs
PW50-3SH35	3	30"	30"	32" x 32"	44 lbs
PW50-4S18	4	40"	18"	20" x 40"	42 lbs
PW50-4S30	4	40"	24"	26" x 40"	44 lbs
PW50-4S35	4	40"	30"	32" x 40"	46 lbs
PW50-4SH18	4	40"	18"	20" x 40"	60 lbs
PW50-4SH30	4	40"	24"	26" x 40"	66 lbs
PW50-4SH35	4	40"	30"	32" x 40"	70 lbs
PW50-5SH18	5	50"	18"	26" x 50"	71 lbs
PW50-5SH30	5	50"	24"	32" x 50"	79 lbs
PW50-5SH35	5	50"	30"	35" x 50"	87 lbs
PW50-6SH18	6	60"	18"	26" x 60"	86 lbs
PW50-6SH30	6	60"	24"	32" x 60"	92 lbs
PW50-6SH35	6	60"	30"	35" x 60"	99 lbs
PW50-7SH18	7	70"	18"	27" x 70"	96 lbs
PW50-7SH30	7	70"	24"	32" x 70"	105 lbs
PW50-7SH35	7	70"	30"	35" x 70"	115 lbs
PW50-8SH30	8	80"	24"	32" x 80"	123 lbs
PW50-8SH35	8	80"	30"	35" x 80"	129 lbs
PW50-9SH30	9	90"	24"	32" x 90"	136 lbs
PW50-9SH35	9	90"	30"	35" x 90"	145 lbs
PW50-10SH30	10	100"	24"	32" x 98"	154 lbs
PW50-10SH35	10	100"	30"	35" x 98"	165 lbs

57° STANDARD SLOPE

Item #	Steps	Platform Height	Step Width	Base W x D	Weight
BS4SH18	4	40"	18"	20" x 34"	55 lbs
BS4SH30	4	40"	24"	26" x 34"	60 lbs
BS4SH35	4	40"	30"	32" x 34"	64 lbs
BS5SH18	5	50"	18"	26" x 42"	65 lbs
BS5SH30	5	50"	24"	32" x 42"	72 lbs
BS5SH35	5	50"	30"	35" x 42"	79 lbs
BS6SH18	6	60"	18"	26" x 48"	78 lbs
BS6SH30	6	60"	24"	32" x 48"	84 lbs
BS6SH35	6	60"	30"	35" x 42"	90 lbs
BS7SH18	7	70"	18"	27" x 55"	88 lbs
BS7SH30	7	70"	24"	32" x 55"	96 lbs
BS7SH35	7	70"	30"	35" x 55"	104 lbs
BS8SH30	8	80"	24"	32" x 61"	112 lbs
BS8SH35	8	80"	30"	35" x 61"	118 lbs
BS9SH30	9	90"	24"	32" x 67"	124 lbs
BS9SH35	9	90"	30"	35" x 67"	132 lbs
BS10SH30	10	100"	24"	32" x 74"	140 lbs
BS10SH35	10	100"	30"	35" x 74"	150 lbs

57° STANDARD SLOPE

Item #	Steps	Platform Height	Step Width	Base W x D	Weight
BS11SH30	11	110"	24"	35" x 83"	148 lbs
BS11SH35	11	110"	30"	38" x 83"	160 lbs
BS12SH30	12	120"	24"	35" x 89"	160 lbs
BS12SH35	12	120"	30"	38" x 89"	172 lbs
BS13SH30	13	130"	24"	37" x 95"	175 lbs
BS13SH35	13	130"	30"	40" x 95"	188 lbs
BS14SH30	14	140"	24"	37" x 102"	190 lbs
BS14SH35	14	140"	30"	40" x 102"	202 lbs
BS15SH30	15	150"	24"	39" x 108"	210 lbs
BS15SH35	15	150"	30"	42" x 108"	224 lbs
BS16SH30	16	160"	24"	39" x 114"	235 lbs
BS16SH35	16	160"	30"	42" x 114"	246 lbs
BS17SH30	17	170"	24"	41" x 120"	267 lbs
BS17SH35	17	170"	30"	44" x 120"	279 lbs
BS18SH30	18	170"	24"	45" x 127"	310 lbs
BS18SH35	18	170"	30"	48" x 127"	335 lbs
BS19SH30	19	190"	24"	48" x 134"	360 lbs
BS19SH35	19	190"	30"	51" x 134"	384 lbs

Mobile Work Platform



Standard Features

- 57 degree industrial slope
- 24" or 30" wide steps
- Tilt & Roll design on 5" rigid casters
- Non-marring rubber tips at stabilizing legs
- Several platform depths (see table)
- 500 lbs load rating
- 1" square steel construction
- 30" handrails if equipped (R shown in item #)
- Gray industrial enamel finish

Optional Items Available

- Deeper top platform
 - Yellow finish or other
 - Top walk-off access with chain or gate
 - California OSHA compliant design
- See "Optional Items" page for more



Item #	Steps	Platform Height	Platform Width	Platform Depth	Base W x D	Weight
2SWP2421	2	20"	24"	21"	26" x 27"	46 lbs
2SWP2428	2	20"	24"	28"	26" x 34"	52 lbs
2SWP2435	2	20"	24"	35"	26" x 41"	58 lbs
2SWP2442	2	20"	24"	42"	26" x 48"	64 lbs
2SWP2449	2	20"	24"	49"	26" x 55"	69 lbs
2SWP2456	2	20"	24"	56"	26" x 62"	76 lbs
2SWP3021	2	20"	30"	21"	32" x 27"	59 lbs
2SWP3028	2	20"	30"	28"	32" x 34"	68 lbs
2SWP3035	2	20"	30"	35"	32" x 41"	77 lbs
2SWP3042	2	20"	30"	42"	32" x 48"	85 lbs
2SWP3049	2	20"	30"	49"	32" x 55"	92 lbs
2SWP3056	2	20"	30"	56"	32" x 62"	102 lbs
3SWP2421	3	30"	24"	21"	26" x 33"	59 lbs
3SWP2428	3	30"	24"	28"	26" x 40"	66 lbs
3SWP2435	3	30"	24"	35"	26" x 47"	73 lbs
3SWP2442	3	30"	24"	42"	26" x 54"	78 lbs
3SWP2449	3	30"	24"	49"	26" x 61"	84 lbs
3SWP2456	3	30"	24"	56"	26" x 68"	91 lbs
3SWP3021	3	30"	30"	21"	35" x 33"	67 lbs
3SWP3028	3	30"	30"	28"	35" x 40"	76 lbs
3SWP3035	3	30"	30"	35"	35" x 47"	84 lbs
3SWP3042	3	30"	30"	42"	35" x 54"	90 lbs
3SWP3049	3	30"	30"	49"	35" x 61"	97 lbs
3SWP3056	3	30"	30"	56"	35" x 68"	106 lbs

Item #	Steps	Platform Height	Platform Width	Platform Depth	Base W x D	Weight
4SWP2421	4	40"	24"	21"	26" x 39"	73 lbs
4SWP2428	4	40"	24"	28"	26" x 46"	80 lbs
4SWP2435	4	40"	24"	35"	26" x 53"	87 lbs
4SWP2442	4	40"	24"	42"	26" x 60"	93 lbs
4SWP2449	4	40"	24"	49"	26" x 67"	98 lbs
4SWP2456	4	40"	24"	56"	26" x 74"	110 lbs
4SWP3021	4	40"	30"	21"	35" x 39"	82 lbs
4SWP3028	4	40"	30"	28"	35" x 46"	90 lbs
4SWP3035	4	40"	30"	35"	35" x 53"	99 lbs
4SWP3042	4	40"	30"	42"	35" x 60"	106 lbs
4SWP3049	4	40"	30"	49"	35" x 67"	113 lbs
4SWP3056	4	40"	30"	56"	35" x 74"	126 lbs
5SWP2421R	5	50"	24"	21"	26" x 45"	87 lbs
5SWP2428R	5	50"	24"	28"	26" x 52"	94 lbs
5SWP2435R	5	50"	24"	35"	26" x 59"	102 lbs
5SWP2442R	5	50"	24"	42"	26" x 66"	108 lbs
5SWP2449R	5	50"	24"	49"	26" x 73"	113 lbs
5SWP2456R	5	50"	24"	56"	26" x 80"	125 lbs
5SWP3021R	5	50"	30"	24"	35" x 45"	96 lbs
5SWP3028R	5	50"	30"	28"	35" x 52"	105 lbs
5SWP3035R	5	50"	30"	35"	35" x 59"	115 lbs
5SWP3042R	5	50"	30"	42"	35" x 66"	121 lbs
5SWP3049R	5	50"	30"	49"	35" x 73"	128 lbs
5SWP3056R	5	50"	30"	56"	35" x 80"	142 lbs

Aluminum Rolling Ladder



Standard Features

- 57 degree industrial slope
- 18" or 24" wide steps
- Tilt & Roll design on 5" rigid casters
- Non-marring rubber tips at stabilizing legs
- 14" deep top platform
- 300 lbs load rating
- 1" square aluminum construction
- 30" handrails if equipped
- Cleaned mill finish

Optional Items Available

- 500 lbs load rating HEAVY DUTY
 - Different caster design
 - Deeper top platform
 - Top walk-off access with chain or gate
 - California OSHA compliant design
- See "Optional Items" page for more

Item #	Steps	Platform Height	Platform Width	Overall Height	Base W x D	Weight
BA2S18	2	20"	18"	20"	20"x18"	16 lbs
BA2S30	2	20"	24"	20"	26"x18"	22 lbs
BA2SH18	2	20"	18"	50"	20"x18"	20 lbs
BA2SH30	2	20"	24"	50"	26"x18"	25 lbs
BA3S18	3	30"	18"	30"	20"x25"	22 lbs
BA3S30	3	30"	24"	30"	26"x25"	29 lbs
BA3SH18	3	30"	18"	60"	20"x25"	25 lbs
BA3SH30	3	30"	24"	60"	26"x25"	32 lbs
BA4S18	4	40"	18"	40"	20"x31"	27 lbs
BA4S30	4	40"	24"	40"	26"x31"	35 lbs
BA4SH18	4	40"	18"	70"	20"x31"	31 lbs
BA4SH30	4	40"	24"	70"	26"x31"	40 lbs
BA5SH18	5	50"	18"	80"	22"x39"	41 lbs
BA5SH30	5	50"	24"	80"	30"x30"	52 lbs
BA6SH18	6	60"	18"	90"	22"x46"	47 lbs
BA6SH30	6	60"	24"	90"	30"x46"	59 lbs
BA7SH18	7	70"	18"	100"	22"x53"	52 lbs
BA7SH30	7	70"	24"	100"	30"x53"	66 lbs
BA8SH30	8	80"	24"	110"	32"x61"	76 lbs
BA9SH30	9	90"	24"	120"	32"x67"	86 lbs
BA10SH30	10	100"	24"	130"	32"x74"	98 lbs

Roll-A-Fold Ladder



Standard Features

- 57 degree industrial slope
- 18" wide steps
- Tilt & Roll design when setup
- 10" semi-pneumatic tires
- Easy folding with 2 bolts
- Non-marring rubber tips at stabilizing legs
- 14" deep top platform
- 300 lbs load rating
- 1" square construction
- 30" handrails if equipped
- Gray industrial enamel finish

Optional Items Available

- 500 lbs load rating HEAVY DUTY
 - Deeper top platform
 - Yellow finish or other
 - Top walk-off access with chain or gate
 - California OSHA compliant design
- See "Optional Items" page for more

Item #	Steps	Platform Height	Platform Width	Base W x D	Weight
PWRF105	5	50"	18"	30" x 45"	80 lbs
PWRF106	6	60"	18"	30" x 52"	100 lbs
PWRF107	7	70"	18"	30" x 59"	155 lbs
PWRF108	8	80"	18"	30" x 64"	126 lbs
PWRF109	9	90"	18"	30" x 72"	140 lbs
PWRF110	10	100"	18"	30" x 78"	159 lbs
PWRF111	11	110"	18"	30" x 85"	175 lbs
PWRF112	12	120"	18"	30" x 92"	195 lbs

Mobile Office Stand



Solid Grip Tape Treads

Perfect for Dress Shoes and Women's Heels

Standard Features

- 57 degree industrial slope
- 18" and 24" wide steps
- Spring-loaded automatic casters
- Non-marring rubber tips at stabilizing legs
- 14" deep top platform
- 300 lbs load rating
- 1" square steel construction
- 30" handrails if equipped
- Gray industrial enamel finish

Optional Items Available

- 500 lbs load rating HEAVY DUTY
 - Deeper top platform
 - Yellow finish or other
 - Top walk-off access with chain or gate
 - California OSHA compliant design
- See "Optional Items" page for more

Item #	Steps	Platform Height	Platform Width	Overall Height	Base W x D	Weight
OL1-S18	1	10"	18"	10"	20"x10"	15lbs
OL1-S30	1	10"	24"	10"	26"x10"	19lbs
OL2-S18	2	20"	18"	20"	20"x20"	28lbs
OL2-S30	2	20"	24"	20"	26"x20"	30lbs
OL2-SH18	2	20"	18"	50"	20"x44"	31lbs
OL2-SH30	2	20"	24"	50"	26"x44"	33lbs
OL3-S18	3	30"	18"	30"	20"x30"	34lbs
OL3-S30	3	30"	24"	30"	26"x30"	37lbs
OL3-SH18	3	30"	18"	60"	20"x60"	38lbs
OL3-SH30	3	30"	24"	60"	26"x60"	41lbs
OL4-S18	4	40"	18"	40"	20"x40"	50lbs
OL4-S30	4	40"	24"	40"	26"x40"	55lbs
OL4-SH18	4	40"	18"	70"	20"x70"	55lbs
OL4-SH30	4	40"	24"	70"	26"x70"	60lbs

Rolling Stock Picker




Standard Features

- 57 degree industrial slope
- 24" wide step standard
- 21" deep top platform
- "Lock-Safe" step lock casters
- Non-marring rubber tips at stabilizing legs
- 300 lbs load rating
- 1" square steel construction
- 30" handrails
- Gray industrial enamel finish

Optional Items Available

- 500 lbs load rating HEAVY DUTY
 - Deeper top platform
 - Yellow finish or other
 - Top walk-off access with chain or gate
 - California OSHA compliant design
- See "Optional Items" page for more



3 Shelf System

- All-welded
- 22" x 22"
- 50 lb. capacity per shelf

Item #	Steps	Platform Height	Base W x D	Weight
SP6SH30W21	6	60"	32"X55"	165lbs
SP7SH30W21	7	70"	32"X62"	175lbs
SP8SH30W21	8	80"	32"X69"	185lbs
SP9SH30W21	9	90"	32"X76"	195lbs
SP10SH30W21	10	100"	32"X83"	205lbs
SP11SH30W21	11	110"	32"X90"	220lbs

Cantilever Ladder

Our most popular design is even better!



Standard Features

- 57 degree industrial slope
- 24" wide steps
- Individual locking casters only
- Counterbalance weight at base
- 300 lbs load rating
- 1" square steel construction
- 30" handrails if equipped
- Gray industrial enamel finish

Optional Items Available

- 500 lbs load rating HEAVY DUTY
 - Deeper top platform
 - Yellow finish or other
 - Top walk-off access with chain or gate
 - California OSHA compliant design
- See "Optional Items" page for more

* Shown with optional Yellow Finish

Item #	Steps	Platform Height	Platform Width	Platform Depth	Overhang	Overall Height	Base W x D
BS8SH30-SP	8	80"	24"	21"	14"	110"	32" x 61"
BS9SH30-SP	9	90"	24"	21"	14"	120"	32" x 67"
BS10SH30-SP	10	100"	24"	21"	14"	130"	32" x 74"
BS11SH30-SP	11	110"	24"	21"	14"	140"	35" x 83"
BS12SH30-SP	12	120"	24"	21"	14"	150"	35" x 89"
BS13SH30-SP	13	130"	24"	21"	14"	160"	37" x 95"
BS14SH30-SP	14	140"	24"	21"	14"	170"	37" x 102"
BS15SH30-SP	15	150"	24"	21"	14"	180"	39" x 108"

Deeper Overhang? Call for a custom design

Maintenance Platform



Standard Features

- 57 degree industrial slope
- 24" wide step standard
- Tilt & Roll design on 5" rigid casters
- Non-marring rubber tips at stabilizing legs
- 21" deep top platform
- 300 lbs load rating
- 1" square steel construction
- 30" handrails
- Gray industrial enamel finish

Optional Items Available

- 500 lbs load rating HEAVY DUTY
 - Deeper top platform
 - Yellow finish or other
 - California OSHA compliant design
- See "Optional Items" page for more

Top Access Safety Chain



Ladders are structurally redesigned to not require a horizontal stabilizing bar. This allows a chain to be unhooked for easy access off and on the platform.

Item #	Steps	Platform Height	Platform Width	Platform Depth	Overall Height	Base W x D	Weight
TMP4SH30	4	40"	24"	21"	70"	32" x 41"	63 lbs
TMP5SH30	5	50"	24"	21"	80"	32" x 49"	78 lbs
TMP6SH30	6	60"	24"	21"	90"	32" x 55"	88 lbs
TMP7SH30	7	70"	24"	21"	100"	32" x 62"	101 lbs

Double-Entry Platform



Standard Features

- 57 degree industrial slope
- 24" and 36" wide serrated treads
- "Lock-Safe" activated casters on both ends
- Non-marring rubber tips at stabilizing legs
- 500 lbs load rating
- 1" square steel construction
- 30" handrails on one side
- Gray industrial enamel finish

Optional Items Available

- 500-1000 lbs load rating HEAVY DUTY
 - Larger top platform size
 - Yellow finish or other
 - California OSHA compliant design
- See "Optional Items" page for more

36" Wide Models					
Item #	Steps	Platform Height	Platform W x D	Base W x D	Weight
PWDE336-49	3	30"	36" x 49"	38" x 77"	198 lbs
PWDE336-63	3	30"	36" x 63"	38" x 91"	214 lbs
PWDE336-70	3	30"	36" x 70"	38" x 98"	228 lbs
PWDE436-49	4	40"	36" x 49"	38" x 89"	225 lbs
PWDE436-63	4	40"	36" x 63"	38" x 103"	242 lbs
PWDE436-70	4	40"	36" x 70"	38" x 110"	256 lbs
PWDE536-49	5	50"	36" x 49"	38" x 105"	252 lbs
PWDE536-63	5	50"	36" x 63"	38" x 119"	274 lbs
PWDE536-70	5	50"	36" x 70"	38" x 126"	297 lbs
PWDE636-49	6	60"	36" x 49"	38" x 117"	299 lbs
PWDE636-63	6	60"	36" x 63"	38" x 131"	314 lbs
PWDE636-70	6	60"	36" x 70"	38" x 138"	329 lbs
PWDE736-49	7	70"	36" x 49"	38" x 131"	328 lbs
PWDE736-63	7	70"	36" x 63"	38" x 145"	345 lbs
PWDE736-70	7	70"	36" x 70"	38" x 152"	362 lbs

24" Wide Models					
Item #	Steps	Platform Height	Platform W x D	Base W x D	Weight
PWDE330-49	3	30"	24" x 49"	26" x 77"	180 lbs
PWDE330-63	3	30"	24" x 63"	26" x 91"	198 lbs
PWDE330-70	3	30"	24" x 70"	26" x 98"	215 lbs
PWDE430-49	4	40"	24" x 49"	26" x 89"	210 lbs
PWDE430-63	4	40"	24" x 63"	26" x 103"	230 lbs
PWDE430-70	4	40"	24" x 70"	26" x 110"	244 lbs
PWDE530-49	5	50"	24" x 49"	26" x 105"	240 lbs
PWDE530-63	5	50"	24" x 63"	26" x 119"	260 lbs
PWDE530-70	5	50"	24" x 70"	26" x 126"	280 lbs
PWDE630-49	6	60"	24" x 49"	26" x 117"	281 lbs
PWDE630-63	6	60"	24" x 63"	26" x 131"	300 lbs
PWDE630-70	6	60"	24" x 70"	26" x 138"	318 lbs
PWDE730-49	7	70"	24" x 49"	26" x 131"	315 lbs
PWDE730-63	7	70"	24" x 63"	26" x 145"	336 lbs
PWDE730-70	7	70"	24" x 70"	26" x 152"	351 lbs

Crossover Platform




Standard Features

- 57 degree industrial slope
- 24" wide steps standard
- Mounting plates or Rubber end caps
- 300 lbs load rating
- 1" square steel construction
- 30" handrails
- Gray industrial enamel finish

Optional Items Available

- 500-1000 lbs load rating HEAVY DUTY
 - Custom clearance height and length
 - Yellow finish or other
 - California OSHA compliant design
- See "Optional Items" page for more



Item #	Steps	Platform Height	Platform W x D	Clearance H x W	Base W x D	Weight
CO4035	4	40"	24" x 35"	37" x 21"	26" x 75"	84 lbs
CO4042	4	40"	24" x 42"	37" x 28"	26" x 82"	89 lbs
CO4049	4	40"	24" x 49"	37" x 35"	26" x 89"	96 lbs
CO5035	5	50"	24" x 35"	47" x 21"	26" x 91"	145 lbs
CO5042	5	50"	24" x 42"	47" x 28"	26" x 98"	151 lbs
CO5049	5	50"	24" x 49"	47" x 35"	24" x 105"	160 lbs
CO6035	6	60"	24" x 35"	57" x 21"	24" x 103"	180 lbs
CO6042	6	60"	24" x 42"	57" x 28"	24" x 110"	186 lbs
CO6049	6	60"	24" x 49"	57" x 35"	24" x 117"	199 lbs

Access Stairway



Standard Features

- 57 degree industrial slope
- 24" wide step standard
- 14" deep top platform
- Mounting brackets at base and landing
- 300 lbs load rating
- 1" square steel construction
- 30" handrails at top
- Gray industrial enamel finish

Optional Items Available

- 500-1000 lbs load rating HEAVY DUTY
 - Custom landing height
 - Wider step size
 - Yellow finish or other
 - California OSHA compliant design
- See "Optional Items" page for more

Item #	Steps	Setup Height	Setup Length	Overall Height	Weight
PWSW4H24	4	40"	34"	70"	40 lbs
PWSW5H24	5	50"	42"	80"	50 lbs
PWSW6H24	6	60"	48"	90"	60 lbs
PWSW7H24	7	70"	55"	100"	71 lbs
PWSW8H24	8	80"	61"	110"	82 lbs
PWSW9H24	9	90"	67"	120"	93 lbs
PWSW10H24	10	100"	74"	130"	105 lbs
PWSW11H24	11	110"	83"	140"	122 lbs
PWSW12H24	12	120"	89"	150"	132 lbs

Custom landing heights are available


Industrial Stairway

Standard Features

- 36 degree gradual slope
- 36" wide x 9.5" deep steps
- Mounting brackets
- 1,000 lbs load rating
- 10" steel channel; 1.5" tubing
- 32" handrails
- Gray industrial enamel finish
- Ships as one welded piece

Optional Items Available


See "Optional Items" page for more



Item #	Landing Height	Rise x Run	Weight
IS36-42G	42"	35" x 48"	240 lbs
IS36-49G	49"	42" x 57"	273 lbs
IS36-56G	56"	49" x 67"	320 lbs
IS36-63G	63"	56" x 76"	370 lbs
IS36-70G	70"	63" x 86"	410 lbs
IS36-77G	77"	70" x 95"	440 lbs
IS36-84G	84"	77" x 105"	494 lbs
IS36-91G	91"	84" x 114"	530 lbs
IS36-98G	98"	91" x 124"	575 lbs
IS36-105G	105"	98" x 133"	620 lbs
IS36-112G	112"	105" x 143"	670 lbs
IS36-119G	119"	112" x 152"	700 lbs

Custom landing heights are available

Fixed Ladders



Standard Specifications

- 22" overall width
- 42" high handrails
- 7" deep wall mounts
- 300 lb. capacity
- Gray enamel finish

Optional Items Available

- Wider or narrower steps or rungs
 - Galvanized finish
 - Aluminum construction
 - "Hatch" caged design with no handrails
- See "Optional Items" page for more

Fixed Ladders				
*Model Options	Item #	Rungs	Rung to Rung H	Overall Width
WT only	FLTP-06	6	60"	24"
WT only	FLTP-07	7	72"	24"
WT only	FLTP-08	8	84"	24"
WT only	FLTP-09	9	96"	24"
CG or WT	FLTP-10	10	108"	24"
CG or WT	FLTP-11	11	120"	24"
CG or WT	FLTP-12	12	132"	24"
CG or WT	FLTP-13	13	144"	24"
CG or WT	FLTP-14	14	156"	24"
CG only	FLTP-15	15	168"	24"
CG only	FLTP-16	16	180"	24"
CG only	FLTP-17	17	192"	24"
CG only	FLTP-18	18	204"	24"
CG only	FLTP-19	19	216"	24"
CG only	FLTP-20	20	228"	24"
CG only	FLTP-21	21	240"	24"

*CG = Caged WT = Walk-Thru (handrails only)

Dock Ladder (Walk-Thru Models)

Item #	Steps	Top Step Height	Overall Width	Weight
DLWT-22	2	18"	22"	36 lbs
DLWT-23	3	30"	22"	40 lbs
DLWT-24	4	42"	22"	44 lbs
DLWT-25	5	54"	22"	48 lbs
DLWT-26	6	66"	22"	52 lbs
DLWT-27	7	78"	22"	56 lbs
DLWT-28	8	90"	22"	60 lbs
DLWT-29	9	102"	22"	64 lbs
DLWT-210	10	114"	22"	68 lbs

Dock Ladder (Side Step Models)

Item #	Steps	Overall Height	Overall Width	Weight
DLSS-26	2	72"	22"	36 lbs
DLSS-27	3	84"	22"	40 lbs
DLSS-28	4	96"	22"	44 lbs
DLSS-29	5	108"	22"	48 lbs
DLSS-30	6	120"	22"	52 lbs
DLSS-31	7	132"	22"	56 lbs
DLSS-32	8	144"	22"	60 lbs
DLSS-33	9	156"	22"	64 lbs
DLSS-34	10	168"	22"	68 lbs

Forklift Work Platforms



Standard Specifications

- 1000 lb capacity
- 42" high handrails with midrail
- 2" x 8" centered fork openings
- 10-gauge steel construction
- Non-skid flooring
- Easy entry swing gate with latch lock

Optional Items Available

- Casters as shown
 - Back cage riser as shown
 - Work shelf
 - Larger platform size
- See "Optional Items" page for more

Item #	Platform Width	Platform Depth	Weight
PWFL-WP36	36"	36"	260 lbs
PWFL-WP36CR	36"	36"	270 lbs
PWFL-WP48	36"	48"	300 lbs
PWFL-WP48CR	36"	48"	310 lbs

Gas Cylinder Cabinets



Standard Specifications

- 12 gauge steel construction
- Expanded metal see-through sides
- Built-in padlock hasp
- Meets OSHA & NFPA standards
- Ships Knock-Down or All-Welded
- Yellow enamel finish

Optional Items Available

- Locking casters at base
 - Custom sizes
 - Higher load rating
 - Special paint finish
- See "Optional Items" page for more

Horizontal Storage Design			
Item #	Cylinder Capacity	Overall W x D x H	Weight
CSC4-4W	4	33"W x 38"D x 40"H	200 lbs
CSC4-8W	8	33"W x 38"D x 71"H	270 lbs
CSC4-12W	12	66"W x 38"D x 71"H	420 lbs
CSC4-16W	16	66"W x 38"D x 71"H	495 lbs
CSC4-4KD	4	33"W x 38"D x 40"H	220 lbs
CSC4-8KD	8	33"W x 38"D x 40"H	290 lbs
CSC4-12KD	12	33"W x 38"D x 40"H	435 lbs
CSC4-16KD	16	33"W x 38"D x 40"H	510 lbs

KD = Knock-Down, W = All-Welded

Vertical Storage Design			
Item #	Cylinder Capacity	Overall W x D x H	Weight
CSCV-20KD	10-20	66"W x 38"D x 71"H	440 lbs
CSCV-10W	5-10	33"W x 38"D x 71"H	255 lbs
CSCV-20W	10-20	66"W x 38"D x 71"H	440 lbs

KD = Knock-Down, W = All-Welded


Optional Items

The following Optional Items listed below all have additional costs. Please consult your price list.



Replacement Parts

2" casters with retaining rings
4" swivel casters
Springs, specify 2" casters or lock safe
5" rigid casters
2" caster box
Bushings
Rubber tips for 1" tube legs



Deeper Top Platform

14" deep
21" deep
28" deep
35" deep
42" deep
49" deep
Call for deeper custom sizes



Wheel Modifications

Taller casters for rough terrain
Wider casters for floor gap clearance
10" pneumatic tires when applicable
Directional locking casters
Easy Turn—6 wheel design



Chain or Gate Access

Back handrails replaced with detachable chain
Side handrails replaced with detachable chain
Back handrails replaced with lockable hinged gate
Side handrails replaced with lockable hinged gate

Handrail Modifications

CAL OSHA—42" handrail, midrail, and 4" toeboards
Add 30" handrails if none are standard
Bolt-on handrails; assembly required
Yellow safety finish on handrails

Work Shelves


Folding 14" deep shelf
Fixed 14" deep shelf



Finish & Color

Yellow enamel finish; quick turnaround
Other finish; specify color or mail paint sample
Galvanized steel finish
Powdercoated finish; specify color

Marine Gangways



- Custom lengths and widths
- Beam type
- Truss type
- Self-adjusting treads →
- Rotating platform
- Gunnale clips
- Davits or Winches
- Bridle and Spreader Bars
- Stowage Brackets





PW Platforms Inc.

4010 Broad Street
Houston, TX 77087
P 800-231-9936
F 713-943-1412

www.pwplatforms.com